

DATA SHEET



ARMOR A-450 GATOR-AID MASTIC ALLIGATORING PATCH

PRODUCT: Armor A-450 Gator-Aid; complying with all applicable V.O.C. emissions tests and E.P.A. standards.

GENERAL: Gator Aid is a blend of an asphaltic emulsion, mineral fillers, glass fiber, ground rubber and plasticizers designed especially for alligatored areas. It is also used for filling cracks in excess of 1/2" in width on any asphaltic surface.

Economical Gator-Aid can be applied as a skin patch directly over alligatored asphalt and shallow pavement depressions without the need of costly asphalt paving equipment or large crews. This ready to use material is perfect for small repairs on asphaltic surfaces such as athletic courts, driveways, playgrounds, walkways, and running tracks.

SURFACE PREPARATION: Pavement surface must be dry and free from all loose material, dirt and dust.

SURFACE

Mix well before using. Use as is. Pour on alligatored areas and work in with squeegee. Broadcast Silica Sand to aid in drying and adhesion to sealer. It is always advisable to use a tack coat (1 part CSS1 H and 6 parts of water) prior to filling alligatored areas, and shallow depressions or bird baths.

FOR FILLING CRACKS: Fill crack in one pour and use a V-shape rubber squeegee to scrape down any excess Gator-Aid remaining on the pavement surface. This last step needs to be performed before the Gator-Aid has hardened.

FOR FILLING BIRD BATHS: Fill area with lifts of 1/4" in depth maximum and allow time to harden before any type of sealcoat application.

Gator-Aid will set-up under good conditions in several hours, depending on weather and filler thickness. Do not use when rain is forecast, when surface is wet or when temperature is below 55°F.

COVERAGE: Gator-Aid will fill up to 20 s/f of alligatored or bird baths areas at 1/4" depth, and up to 75 linear feet of 2" wide x 2" deep cracks.

COLOR: Jet Black upon drying.

CAUTION: Wash tools in water. Use a paint thinner if material has dried. Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100 F. Container should be closed when not in use. Keep out of the reach of children.

PACKAGING: Five gallon pails.
For additional technical information, please write or call Armor Manufacturing.

