

# DATA SHEET



## ARMOR PETRO SEAL – OIL SPOT PRIMER # A-500



**PRODUCT:** Petro Seal #A-500 oil spot primer for asphalt surfaces.

**DESCRIPTION:** Petro Seal is a quick drying Latex Emulsion formulated with additives which provide a protective barrier for sealer over oil, grease, gasoline or chemical spills. Always apply Petro Seal to damaged areas prior to the application of Armor Seal Asphalt Base, or Coal Tar Base Sealer. Petro Seal can be used on any asphalt surface, including parking lots, driveways, airport runways and aprons, traffic safety islands and golf cart paths.

**PREPARATION:** Scrape off and remove excessive build up of oil, grease or other chemicals before application.

**APPLICATION:** Mix well before using. Dilute with water 2 to 1. On heavy oil spills mix 1 to 1. Allow to completely cure before sealing.

**COVERAGE:** One gallon covers approximately 200 square feet.

**PACKAGING:** 5 Gallon Pails

**CLEAN UP:** Wash tools in water. Use kerosene if material has dried.

**COLOR:** Clear, when dry.

**HANDLING:** Stir before using. Keep from freezing. Do not store in direct sunlight or where temperatures exceed 100 degrees F. Do not apply when temperatures are below 50 degrees F, or if rain is evident or forecast. Containers should be closed when not in use.